



EVPRO1

4K60 NDI PTZ Camera with 12x Zoom and Auto Tracking

The EVERET EVPRO1 is a high quality UHD 4K60 NDI/HDMI/3G-SDI PTZ Camera with 12x optical zoom and Ultra Wide Viewing Angle 80.5°. Equipped with a professional 1/2.8" SONY CMOS sensor to capture every detail even in low-light conditions.

Features:

- ▶ Capture up to UHD 4KP60 with 12x optical zoom
- ▶ Sony IMX415 1/2.8 inch 8.42 MP UHD CMOS sensor
- ▶ Ultra Wide Viewing Angle 80.5°
- ▶ Superior High Performance Ambarella ISP chipset
- ▶ NDI High-Quality Video with Low-Latency
- ▶ Offers support for both NDI®|HX2 (4K) and NDI®|HX3 (up to FHD)
- ▶ NDI High Quality Video with low latency, compatible with NDI version 5.5
- ▶ Simultaneous Quad Output*;
NDI®|HX, HDMI, UVC USB and 3G-SDI compatible with Blackmagic Design SDI Level-B
- ▶ Power over Ethernet (PoE) support: get video, control and power supply with one CAT5/6 cable
- ▶ Automatic NDI® Tally Support
- ▶ Supplied with functional IR remote controller
- ▶ Flexible mounting options with image flip function, support upside-down installation
- ▶ OSD menu, IP address, streaming resolution and size can be set in OSD menu
- ▶ 3 year warranty

Product specifications

Camera	EVPRO1
Sensor	Sony IMX415 1/2.8 inch 8.42 MP CMOS Sensor
Color Space	8bit RGB 4:4:4; ISP RAW (12bit)
Video	
Video Interface	HDMI 2.0 / 3G-SDI* / USB 2.0 (type-c) / RJ45 (IP) *Level A and B
Video Encoding	H.264/H.265
Streaming Protocols	NDI® HX2 / NDI® HX3** / RTMP / SRT / RTSP **max resolution 1080p60
Bitrate control	Variable or Constant
Video Bitrate	1024Kbps ~ 61440Kbps
I-Frame Interval	1 - 120
Audio	
Interface	3.5mm Line-in
Samplerate	AAC: 16000Hz – 48000Hz LPCM: 11025Hz – 48000Hz
Bitrate for AAC	32000Kbps – 128000Kbps
Volume	1-100
Video format	
HDMI	3840x2160 P60/50/30/25 29.97/ 24/23.98 1920x1080P60/50/30/25/59.94/29.97/24/23.98 1920x1080i60/50/59.94 1280x720P60/50/30/25/59.94/29.97
3G-SDI	1920x1080P60/50/30/25/59.94/29.97/24/23.98 1920x1080i60/50/59.94 1280x720P60/50/30/25/59.94/29.97
USB 2.0 (type-C)	NV12: 1920*1080P5 1280*720P15 1024*576P25 800x480P30 YUYV: 1920*1080P5 1280*720P15 1024*576P25 800x448P30 MJPG: 3840x2160P30 1920x1080P60 1280x720P60 1024x576P60 800x448P60 H264 /H265: 3840x2160P30 1920x1080P60 1280x720P60 1024x576P60 800x448P60
NDI® HX3	Main Stream: 1920x1080@15~60 1280x720@15~60 1024x276P60/50 Sub Stream: 640x360@30

Product specifications

Camera	EVPRO1
NDI® HX2/RTMP/SRT/RTSP	Main Stream: 3840x2160@15~60 1920x1080@15~60 1280x720@15~60 1024x576@15~60 Sub Stream: 640x360@30
Lens	
Optical Zoom	12x
Digital Zoom	4x
Aperture	F1.8(Wide)~F3.6(Tele)
Focal Length	f= 3.4mm~40.3 mm
Horizontal Viewing Angle	80.5°(Wide)~7.6°(Tele)
Vertical Viewing Angle	50.0°(Wide) ~ 4.4°(Tele)
Diagonal Viewing Angle	88.9° (Wide) ~ Tele: 8.7° (Tele)
PTZ	
Speed by Zoom	ON/OFF
Pan/Tilt rotation range	Pan: -170° ~+170° Tilt: 30°~+90°
Pan/Tilt rotation speed	Pan: 0.1°~80°/s Tilt: 0.1°~60°/s
PTZ Freeze	Yes
Pan & Tilt Speed	5 - 24
Zoom Speed	1 - 7
Presets	IR Remote : 10, WebUI: 128, EVKB200N: 128, Serial: 128
Save AE & WB settings in preset	ON/OFF
Preset Speed Pan & tilt	5 - 24
Preset Speed Zoom	1 - 7

Product specifications

Camera	EVPRO1
Image	
Shutter Speed	1/1 – 1/10000s
Iris	F1.8 - F14
Minimum Object distance	Wide: 1m~INF; Tele: 1.5m~INF
Video S/N Ratio	>50dB
Minimum Illumination	0.5lux (50 IRE Max AGC,1/30,F1.8)
Focus	Auto / Manual / One Push Auto Focus
Gain Level	0-30Db
White Balance Modes	Auto / Manual / Auto Tracking / One Push / Indoor / Outdoor / Colour Temperature
Exposure Modes	Auto / Manual / Shutter Priority / Iris Priority / Brightness Priority
Wide Dynamic Range Level	Levels 1-6
Gamma	Levels 0-8
Anti-Flicker	OFF / 50Hz / 60Hz
3D NR	OFF / Auto / Level 1-4
2D NR	Yes
Image Flip	Yes
Image Mirror	Yes
Back Light Compensation	Yes
Tally Light	Yes

Product specifications

Camera	EVPRO1
Control	
Network (RJ45)	NDI / HTTP / ONVIF / VISCA over IP (TCP&UDP) / HTML5 (WebUI)
Serial	RS232 / RS422 / RS485 / PELCO P/D
IR Remote	Yes
Daisy Chain	Yes, up to 7 cameras
USB	USB2.0 (UVC1.1)
Visca over IP Port	52381
NDI Port	5961
Network	
Default IP	192.168.1.188
Port Speed	1 Gb/s
PoE	POE+(IEEE802.3at)
DHCP	Yes
Multicast	Yes
NDI Discovery Server	Yes
HTTP Port	80
RTSP Port	554
RTSP Encrypt	Yes
General	
Environment	Indoor
Operating Temperature	-10°C~50°C
Operating Humidity	≤80%

Product specifications

Camera	EVPRO1
Power input	DC12V/POE+(IEEE802.3at)
Power Consumption	PoE+ : 9W, DC in: 9W
Dimensions (LxWxH)	205mm×165mm×191.8mm
Weight	1.5 KG
EAN (EVPRO1 Black)	8720387387410
EAN (EVPRO1W White)	8720387387427

**Everet Imaging**

Kraanspoor 50
1033 SE Amsterdam
The Netherlands

+31(0)20 798 6654
www.everetimaging.com
info@everetimaging.com

twitter: @everetimaging

facebook: everetimaging

